



Sonde de courant H32.UE 3000A / 1V

The H32.UE 3000A / 1V current probe has been designed for use with multimeters, recorders, safety testers etc. for accurate non intrusive measurement of AC current. Using the latest transformer technology, the H32.UE 3000A / 1V probe can measure currents from 10A to 3000A over a frequency range of 30Hz to 10kHz.



Electrical Characteristics

Current Range I_N	: 3000 A_{RMS}
Measuring Range.....	: 10 A to 3600 A_{RMS}
Output Sensitivity.....	: 0.333 mV / A
Load Impedance.....	: ≥ 100 kOhm
Conductor Position Sensitivity.....	: 1.5% @ 50Hz
Error due to adjacent conductor.....	: ≤ 6 mA / A @ 50 Hz
Phase shift at 2kHz @ 10A.....	: 3°
Frequency Range.....	: 30 Hz to 10 kHz
Temperature Coefficient.....	: 0.01% / °C
Working Voltage (see Safety Standards section).....	: 600 V AC_{RMS} or DC

Accuracy

3000A

Primary Current	10 to 100A	100 to 300A	300 to 1000A	1000 to 3600A
Accuracy (of rdg)	2.5% +2 mV	1.5%	0.75%	0.5%
Phase Error	Not specified	1.5°	0.75°	0.5°

General Characteristics

Maximum Conductor Size.....	: 72 mm diameter
Output Connection.....	: 4 mm socket
Operating Temperature Range.....	: -10 to +55 °C
Storage Temperature Range.....	: -40 to +70°C
Operating Humidity.....	: $\leq 85\%$
Weight.....	: 1800 g

Reference conditions: Temperature : +18°C to 26 °C, humidity: 20 to 75% RH, sinusoidal current: 48 to 65Hz, distortion factor: < 1%, DC current: none, DC magnetic field: 40 A/m earth's magnetic field, alternating magnetic field: none, proximity of external conductor: none, primary conductor: centred in the aperture, load impedance: $\geq 1\text{M}\Omega$, <100pF for voltage output.

Safety Standards

IEC61010-1: 2010
IEC61010-2-032: 2012
IEC61010-2-031: 2008

600 V_{RMS}, Category III, Pollution Degree 2

Use of the probe on **uninsulated conductors** is limited to 600 V AC_{RMS} or DC and frequencies below 1 kHz.

EMC Standards

EN 61326 :1998

Dimensions

