



## Current probe M3.UB 10A / 2V

The M3.UB 10A / 2V current probe has been designed for use with multimeters, recorders, safety testers etc. for accurate non intrusive measurement of AC current. Using the latest transformer technology, the M3.UB 10A / 2V can measure currents from 10mA to 10A over a frequency range of 30Hz to 10kHz.

The very small head facilitates the insertion of the probe in places where ease of access is of crucial importance.



### Electrical Characteristics

Current Range $I_N$ .....	: 10 A AC <sub>RMS</sub>
Measuring Range.....	: 10mA to 10A <sub>RMS</sub>
Output Sensitivity .....	: 200mV / A
Load Impedance .....	: > 1 MOhm
Conductor Position Sensitivity.....	: < 0.5% @ 50/60Hz
Phase Shift at 2 kHz @ 10A .....	: not specified
Frequency Range .....	: 30 Hz to 10 kHz
Temperature Coefficient.....	: 0.015% / °C
Working Voltage (see Safety Standards section) .....	: 600 V AC <sub>RMS</sub> or DC

### Accuracy

Primary Current	10mA to 50mA	50mA to 100mA	100mA to 10A
Accuracy (of rdg)	5%	2%	1%
Phase shift (typ)	Not specified	7°	5°

### General Characteristics

Maximum Conductor Size.....	: 15 mm diameter, bus bar 15 x 17mm
Output Connection.....	: Safety sockets 4mm
Operating Temperature Range .....	: -10 to +55 °C
Storage Temperature Range .....	: -20 to +70 °C
Operating Humidity .....	: 15% to 85% (non condensing)
Weight.....	: 165 g

**Reference conditions:** Temperature : +18°C to 26 °C, humidity: 20 to 75% RH, sinusoidal current: 48 to 65Hz, distortion factor: < 1%, DC current: none, DC magnetic field: 40 A/m earth's magnetic field, alternative magnetic field: none, proximity of external conductor: none, primary conductor: centred in the aperture, load impedance:  $\geq 1\text{M}\Omega$ ,  $< 100\text{pF}$  for voltage output.

## Safety Standards

IEC61010-1:2010

IEC61010-2-032:2012

IEC61010-2-031:2008

600 V<sub>RMS</sub>, Category III, Pollution Degree 2

Use of the probe on **uninsulated conductors** is limited to 600 V AC<sub>RMS</sub> or DC and frequencies below 1 kHz.

## EMC Standards

EN 61326 :1998

## Dimensions

in mm

