



Current Probe S.V 1000A / 1V_{DC}

The S.V 1000A / 1V_{DC} current probe has been designed for use with multimeters, recorders, power analysers, safety testers etc. for accurate non intrusive measurement of AC current. Using the latest transformer technology, the S.V 1000A / 1V_{DC} can measure currents from 10A to 1200A over a frequency range of 30Hz to 10kHz.



Electrical Characteristics

Current Range : 1000 A_{RMS}
Continuous Measuring Range : 10 A to 1200 A_{RMS}
Output Sensitivity : 1 mV_{DC} / A
Load Impedance (ohm)..... : ≥ 100 kOhm
Frequency Range : 30 Hz to 10 kHz
Temperature coefficient..... : 0.01% / °C
Working Voltage (see Safety Standards section) : 600 V AC_{RMS} or DC

Accuracy

Primary current	10 à 100 A	100 à 1000A
Accuracy (of rdg)	±3% ±1mV	±1%

General Characteristics

Maximum Conductor Size : 50 mm diameter
Output Connection : 4mm safety sockets
Operating Temperature Range : -10 to +55 °C
Storage Temperature Range : -40 to +70 °C
Operating Humidity : 15% to 85% (non condensing)
Weight..... : 620 g

Reference conditions: Temperature : +18°C to 26 °C, humidity: 20 to 75% RH, sinusoidal current: 48 to 65Hz, distortion factor: < 1%, DC current: none, DC magnetic field: 40 A/m earth's magnetic field, alternating magnetic field: none, proximity of external conductor: none, primary conductor: centred in the aperture, load impedance: $\geq 1\text{M}\Omega$, <100pF for voltage output.

Safety Standards

IEC61010-1: 2010
IEC61010-2-032: 2012
IEC61010-2-031: 2008

600 V_{RMS}, Category III, Pollution Degree 2

Use of the probe on **uninsulated conductors** is limited to 600 V AC_{RMS} or DC and frequencies below 1 kHz.

EMC Standards

EN 61326 :1998

Dimensions

