

Current Probe SC.2C 200A / 1V

The SC.2C 200A / 1V current probe is based on Hall Effect technology for use in measurement of both DC and AC current. The SC.2C 200A / 1V may be used in conjunction with multimeters, recorders and other suitable equipment for accurate non intrusive current measurement.



Electrical Characteristics


Current Range	: 200 A AC _{RMS} or DC
Measuring Range.....	: 5 A to 240 A
Output Sensitivity	: 5 mV/A
Resolution	: ± 100 mA
Load Impedance	: ≥ 1MΩ and ≤ 100 pF
Bandwidth	: DC to 10 kHz (-3dB)
Conductor Position Sensitivity.....	: ± 1.5% relative to centre reading
Temperature Coefficient	: ± 0.1% of reading / °C
Power Supply	: 9 V Alkaline, MN1604/PP3
.....	: 75 Hours, low battery indicator
Working Voltage (see Safety Standards section)	: 600 V AC _{RMS} or DC

Accuracy

Primary Current	5 à 20 A	20 à 50 A	50 à 100A	100 à 200 A
Accuracy (of rdg)	±2%±5 mV	±2%	±1%	±1%
Phase Error (typ)	<2°	<1°	<1°	<1°

General Characteristics

Maximum Conductor Size	: 50 mm diameter
Output Connection	: 4mm sockets
Zero	: Manual adjust via thumbwheel
Operating Temperature Range	: 0 to +50 °C
Storage Temperature Range (with battery removed).....	: -20 to +85 °C
Operating Humidity	: 15% to 85% (non condensing)



Reference conditions: Temperature : +18°C to 26 °C, humidity: 20 to 75% RH, sinusoidal current: 48 to 65Hz, distortion factor: < 1%, DC current: none, DC magnetic field: none, alternating magnetic field: none, proximity of external conductor: none, primary conductor: centred in the aperture, load impedance: $\geq 1\text{M}\Omega$, <100pF for voltage output.

Safety Standards


IEC61010-1: 2010
IEC61010-2-032: 2012
IEC61010-2-031: 2008

600 V_{RMS}, Category III, Pollution Degree 2

Use of the probe on **uninsulated conductors** is limited to 600 V AC_{RMS} or DC and frequencies below 1 kHz.

Dimensions

in mm



Note : version shown with cable output

Specifications subject to change without notice