



Current Probe S 250 500 1000A / 5A

The S 250 500 1000A / 5A current probe has been designed for use with multimeters, recorders, power analysers, safety testers etc. for accurate non intrusive measurement of AC current. Using the latest transformer technology, the S 250 500 1000A / 5A can measure currents from 1A to 1200A over a frequency range of 30Hz to 10kHz.



Electrical Characteristics

Current Range	: 250 / 500 / 1000 A _{RMS}
Continuous Measuring Range	: 1 A à 1.2 x I _N
Output Sensitivity	: 20 mA / A (250 A)
.....	: 10 mA / A (500 A)
.....	: 5 mA / A (1000 A)
Load Impedance (ohm).....	: ≤ 0.5 Ohm (250 A)
.....	: ≤ 1 Ohm (500 A)
.....	: ≤ 1 Ohm (1000 A)
Conductor Position Sensitivity.....	: 0.5% @ 50Hz
Error due to adjacent conductor	: ≤ 2mA / A @ 50 Hz
Frequency Range	: 30 Hz to 10 kHz
Temperature coefficient	: 0.01% / °C
Working Voltage (see Safety Standards section)	: 600 V AC _{RMS} or DC

Accuracy

250A

Primary current	1 à 25 A	25 à 50A	50 à 150A	150 à 300A
Accuracy (of rdg)	5% +5 mA	4%+2 mA	3%	2.5%
Phase shift (typ)	Pas précisé	8°	6°	4°

500A

Primary current	10 à 50A	50 à 100A	100 à 600A
Accuracy (of rdg)	3.5%	2.5%	2%
Phase shift (typ)	6°	4°	3°

1000A

Primary current	10 à 50A	50 à 100A	100 à 500A	500 à 1200A
Accuracy (of rdg)	2.5%	2%	1.5%	1%
Phase shift (typ)	4°	3°	2°	1°

General Characteristics

Maximum Conductor Size	: 50 mm diameter
Output Connection	: 4mm safety sockets
Operating Temperature Range	: -10 to +55 °C
Storage Temperature Range	: -40 to +70 °C
Operating Humidity	: 15% to 85% (non condensing)
Weight.....	: 620 g

Reference conditions: Temperature : +18°C to 26 °C, humidity: 20 to 75% RH, sinusoidal current: 48 to 65Hz, distortion factor: < 1%, DC current: none, DC magnetic field: 40 A/m earth's magnetic field, alternating magnetic field: none, proximity of external conductor: none, primary conductor: centred in the aperture, load impedance: $\leq 1\Omega$ for current output.

Safety Standards

IEC61010-1: 2010
IEC61010-2-032: 2012
IEC61010-2-031: 2008

600 V_{RMS}, Category III, Pollution Degree 2

Use of the probe on **uninsulated conductors** is limited to 600 V AC_{RMS} or DC and frequencies below 1 kHz.

EMC Standards

EN 61326 :1998

Dimensions

